

# CT-1 Carbide Saw Tipping System



## Features

- Semi-automatic or manual operation
- Stepper motor package rotates blade to correct location during brazing process; skips every other tooth to avoid over heating blade; makes two passes to complete blade
- Precise  $\pm 0.002$ " alignment of carbide tips on center of saw blade body
- Quick, clean induction heating system consistently produces high quality braze joints
- Pneumatic sled on coil to move coil back to allow for easy blade load/unload
- Convenient touch screen for machine control and process setup
- Timing page for setting programs for different blades
- Cassette feeder for carbide tips or optional bowl feed
- Designed to work with or without pre-tinned carbides
- Pneumatic braze paste or flux dispensing system
- Robust steel frame with leveling pads or casters

## Specifications

- 5.6 kW solid-state low voltage generator
- 100 bit capacity carbide tip magazine
- Track-adjustable tip track assembly for quick setting
- Accepts 6" - 20" diameter saw blades
- Requires 80 PSI air pressure
- Base machine weight: 950 lbs.
- Dimensions: 45" wide, 32" deep, 46" high
- 220/1/60 electric, to UL/CSA Standards, 30 Amp circuit required with 6kW power source and other standard accessories

## Options

- Infrared pyrometer for consistent regulation of brazing temperature
- Water chiller unit, 6000 BTU or 1.76 Kwh

## For More Information

INDUCTION ATMOSPHERES  
35 Industrial Park Circle, Rochester, NY USA 14624  
Tel: 585.368.2120 • Fax: 585.368.2123  
Email: [info@inductionatmospheres.com](mailto:info@inductionatmospheres.com)  
Web: [www.inductionatmospheres.com](http://www.inductionatmospheres.com)

© 08/2008 Induction Atmospheres LLC  
All information subject to change without notice.



Proudly Designed,  
Engineered and  
Built in USA